

```

mail -service.xml
<?xml version="1.0" encoding="UTF-8"?>
<!-- $Id: mail -service.xml 62349 2007-04-15 16:48:15Z dimi tris@jboss.org $ -->
<server>

<!-- ===== -->
<!-- Mail Connection Factory -->
<!-- ===== -->

<mbean code="org.jboss.mail.MailService"
  name="jboss:service=Mail">
  <attribute name="JNDIName">java:/Mail</attribute>
  <attribute name="User">pacchu.p</attribute>
  <attribute name="Password">akshanth1234</attribute>
  <attribute name="Configuration">
    <!-- A test configuration -->
    <configuration>
      <!-- Change to your mail server protocol -->
      <property name="mail.store.protocol" value="pop3"/>
      <property name="mail.transport.protocol" value="smtp"/>

      <!-- Change to the user who will receive mail -->
      <property name="mail.user" value="pacchu.p@gmail.com"/>

      <!-- Change to the mail server -->
      <property name="mail.pop3.host" value="pop.gmail.com"/>

      <!-- Change to the SMTP gateway server -->
      <property name="mail.smtp.host" value="smtp.gmail.com"/>
      <property name="mail.smtp.starttls.enable" value="true" />
      <property name="mail.smtp.socketFactory.class"
value="javax.net.ssl.SSLSocketFactory" />

      <!-- The mail server port -->
      <property name="mail.smtp.port" value="465"/>
      <property name="mail.smtp.socketFactory.port" value="465" />

      <!-- Change to the address mail will be from -->
      <property name="mail.from" value="pacchu.p@gmail.com"/>
      <property name="mail.smtp.user" value="pacchu.p@gmail.com"/>
      <property name="mail.smtp.password" value="akshanth1234"/>
      <property name="mail.smtp.auth" value="true"/>

      <!-- Enable debugging output from the javamail classes -->
      <property name="mail.debug" value="false"/>
    </configuration>
  </attribute>
  <depends>jboss:service=Naming</depends>
</mbean>

<!-- OpenKM -->
<mbean code="org.jboss.mail.MailService" name="jboss:service=OpenKM">
  <attribute name="JNDIName">java:/mail/OpenKM</attribute>
  <attribute name="User">nobody</attribute>
  <attribute name="Password">password</attribute>
  <attribute name="Configuration">
    <configuration>
      <property name="mail.transport.protocol" value="smtp"/>
      <property name="mail.smtp.host" value="localhost"/>
      <property name="mail.smtp.port" value="25"/>
      <property name="mail.from" value="noreply@openkm.com"/>
      <property name="mail.debug" value="true"/>
    </configuration>
  </attribute>
  <depends>jboss:service=Naming</depends>
</mbean>
</server>

```